


## Physical Specifications

<b>Packed Dimensions:</b>	<b>W</b>	<b>H</b>	<b>D</b>	
	711mm	508mm	737mm	
	28"	20"	29"	
<b>Unit Dimensions:</b>	<b>W</b>	<b>H</b>	<b>D</b>	
	445mm	178mm	593mm	
	17.52"	7"	23.35"	
<b>Unit + Rack Handles</b>			<b>D</b>	
			621mm	
			24.45"	
<b>Rack Depth:</b>			<b>D</b>	
			585mm	
			23.03"	
<b>Unit Weight:</b>		19.5kg	43lbs	
<b>Packed Unit Weight:</b>		26kg	57lbs	

**Bundled Accessories:**  
 Keyboard, Mouse & Pad, Power Cable (Plug-True1), Power Daisy Chain (True1-True1), Active DP to DVI adapter, Getting Started Guide + Manual, Backmounted Rails.

## Hardware Specifications

<b>Voltage:</b> 100-240V, 50-60Hz	<b>Memory:</b> 32GB DDR3 ECC RAM	<b>Audio:</b> RME Professional
<b>Power Consumption:</b> 800W @ 110V (normal) 1000W @ 110V (max)	<b>Environmental Tolerances:</b> Temperature: 5-35°C (40°-95°F) Humidity: 5%-95% (non-condensing) Altitude: 0-8850 ft (0-2700m)	<b>Storage:</b> 2 × 80GB SSD (Internal System Drive, Restore Drive) 2TB Removable SSD RAID Array (expandable)
<b>Operating System:</b> Windows 8.1 Embedded Pro	<b>Mounting System:</b> 4U 19" rack mount	
<b>CPU:</b> 2 × Xeon Hexa-Core 3.5Ghz		

## System Connectivity I/O

<b>Video Output:</b> 4 × DisplayPort 1.2 (Stage) (4096 × 2160 max) 1 × DisplayPort 1.2 (GUI) Different VFC cards available	<b>Analogue Audio:</b> 2 × Balanced XLR Output 2 × Balanced XLR Input 1 × 1/4" Headphones Jack	<b>Artnet:</b> 1 × Gigabit LAN
<b>Video Input:</b> 4 × HD-SDI or 2 × 3G-SDI	<b>Digital Audio:</b> ADAT/SPDIF I/O	<b>Media Network:</b> 2 × 10Gb/sec LAN
	<b>MIDI:</b> 1 × In, 1 × Out	<b>Data/Peripherals:</b> 2 × USB 2.0 3 × USB 3.0
	<b>General Network:</b> 1 × Gigabit LAN	<b>Video Sync:</b> BNC Genlock

## Media File Specifications

**Video Playback:**  
 .mov (anim, pjpg, DXV, Hap, Hap Q)  
**Image Formats:** .bmp, .jpg, .png, .tiff, .tga  
**Audio Playback:**  
 .wav/.mp3 (44.1kHz, 16-bit, stereo)  
**3D Mesh Format:** .obj

## Support, Updates and Warranties

**Licence subscription package includes:**  
 – Free software upgrades for the life of the machine  
 – 2 year return to base hardware warranty (plus options to extend warranty length)  
 – Free support (via phone or email)